

#370

J

k

Revision J,

2016

Resource Library
Safety Data Sheets (SDS)
Video Library

Serie

Serie

Fin

Serie

#710

#770

#610

#630

#620

#613

#690

#510

#530

#310

Gr

#370

#280

Cl

#220

3/4 x 24

x

5 1/2 x

5 1/2

x

6 x 24

xx

xxxx

2 x 30

x

3 x 30

x

4 x 30

xx

6 x 30

xx

24 x 30

xx

3/4 x 60
x
1 x 60
xxxxxxxxx
2 x 60
xxxxxxxxx
3 x 60
x
4 x 60
xxxxxxxxx
6 x 60
x
xxxxxx
12 x 60
x
xxxxxx
18 x 60
xx
x
x
24 x 60
xxxxx
36 x 60
x
xx
48 x 60
xxx

3

3M Safety-Walk

X -

0

-

*

-

Type of 3M Safety-Walk Slip-Resistant Tapes and Treads

700

600

Serie

300

200

xx0

xx0

x0

ATVs

xx0

xx0

xx0

x0

Buses

xx0

x

x

xx

x

x

xx

x

3M Safety-Walk

Type of 3M Safety-Walk Slip-Resistant Tapes and Treads

700

500

Color

#710

#770

#610

#630

#620

#613

#6 90

#310

#

370

#220

#280

(g)/m

2

5.50

1,700

2.4

730

2.4

730

2.4

730

2.4

730

2.8

850

2.7

830

2.1

640

40 F (4 C)40 F (4 C)40 F (4 C)40 F (4 C)40

F (4 C)40 F (4 C)40 F (4 C)50 F (10 C)

3M-SW-29.0 -

175 F

(79 C)

175 F

(79 C)

150 F

(66 C)

150 F

(66 C)

150 F
(66 C)
175 F
(79 C)
175 F
(79 C)
150 F
(66 C)
ASTM E648-1
0e1
or
(NFPA253)

-

-

W/cm
2

-

NFPA

1.02

I

1.01

I

630:

1.02

I

620:

0.99

1

1.01

I

1.01

I

1.02

I

0.37

II

1.01

I

2010 IMO

FTP,

U.S Coast

Guard

Approval

Number:

164.117/

50/0

FAA 25.855-F-1 -

T3003

(

)

FAA 25-8 53-F-1 -

T3003

ASTM E662-09 o
(NFPA258) -

-
-

Pass
Pass

73
174
98
97

630:
47
47

620:
60
40

53
47
s

90
32
57
65

78
244

177
164
Sensor

700
#610

#630,
#620

#613,
#690

500
300

200
1.05
1.00
0.76
1.04
1.02
0.87
1.02
1.05
0.90
1.02
1.05
0.90
1.04

0.94
0.95
1.06
0.83
0.31
1.29
0.86
0.35
0.65
0.83
N/A
0.74
1.19
N/A
0.78
1.14
N/A
N/A
N/A
N/A
0.72
1.14
N/A
0.73
0.77
N/A
0.66
0.79
N/A
Sensor

700

#610

#630,
#620

#613,
#690
500

300

200
1.24
1.14
1.05
1.40
1.30
1.17
1.30
1.25
1.31
1.30
1.25
1.31
1.38
1.25
1.28
1.06
0.84
0.51
1.38

0.81
0.58
0.90
1.05
N/A
1.00
1.64
N/A
1.05
1.48
N/A
N/A
N/A
N/A
1.04
1.46
N/A
0.81
0.81
N/A
0.82
0.93
N/A

5

3M Safety-Walk Slip
-Resistant Materials

R -

I -

IC -

NR

-

DIN9Ger.51130 (ZH1/571):

700

#610

#630,
#620

#613,
#690

50
0

300

200

R
1
3-----

V
8-----

3M

Safety-Walk

700

600

500

300

200

Color
#710
#770
#610

#630

#620

#613

#6 90

#510

#530

#310

#370

#220

#280

RRRRRRRR

RRRIIRRR

1%

RRRRRRRR

1%

IIN

R II N

RRR

RRRN

RN

RRRR

RRRIIRRR

RRR II RRI

RRRRRRRR

(Skydrol 500B)

NR

NR

R

R

R

I

R

NR

RRRRRRRR

IIIIIIIN

R

R

R

NR

I

I

NR

NR

NR

NR

NR

IC

NR

NR

NR

NR
NR

RRIR RI
CRR

RRRIRRRR
RRRRRRRR
RRIIIN
RN
R

RRRRRRRR

6

3M Safety-Walk

1 -

2 -

3 -

4 -

1.

40 F (4 C)

40 F (4 C)

40 F (4 C)

40 F (4 C)

50 F (10 C)

:

xN
o

xxN
o

x

xN
o

xN
o

x

7

3M Safety-Walk

i

k

P

-

-

-

-

k

i

O

3M Commercial Solutions
3M Center, Building 220-12E-04
St. Paul, MN 55144
Phone 1-800-328-0033
Web 3M.com/Facility

3M Safety-Walk

i

J DEC-2016: