

PRODUCT CATALOG

■ New Products

NEW

■ Sound Level Meter

■ Vibration Meter

■ Light Meter

■ Humidity Temperature Meter

■ Particle Counter

■ CO/ CO₂ Tester

■ Infrared Thermometer

■ Thermometer

■ EMF Tester

■ PH Meter

■ Power Clamp Meter

■ Harmonic Clamp Meter

■ Battery Impedance Tester

■ Solar Power Meter

■ Flexible Clamp Meter

■ Anemometer/ Tachometer

■ Multimeter

■ Milli / Micro Ohm Meter

■ Earth/ Ground Tester

■ Insulation tester

■ Clamp Meter

■ Calibrator

■ Lan Cable Tester

■ Power Supply

■ Accessories

► **Sound Level Meter**

Home > Products > DC/AC Sound Level Meter > Integrating Sound Level Meter(USB)



TES-1353S

Integrating Sound Level Meter(USB)

Product Features

- Compliant with IEC 61672-1 class2 standard.
- Easy to use for Equivalent continuous sound pressure level, Sound exposure level, Percentile level, Maximum level and Minimum level can be measured simultaneously.
- Dynamic range of 60dB
- Five range from 30 to 130dB
- A&C Frequency Weighting
- Impulse/Fast/Slow dynamic characteristic
- 200M Records Data logging function (microSD CARD 4GB)
- USB interface
- Sound Level Alarm Output
- Real time clock with calendar

Applicable standards	IEC61672-1: 2013 Class 2, ANSI S1.4: 1983 Type 2
Measurement item	SPL, Leq, SEL, MaxL, MinL, Peak, Ln (5%, 10%, 50%, 90%, 95%)
Measurement level	30dB to 130dB
Linearity range	60dB
Measurement frequency range	31.5 Hz to 8KHz
Frequency weight	A and C
Time weight	Fast, Slow and Impulse
Accuracy	±1.0dB (ref 94dB @1KHz)
Microphone	1/2 inch Electret condenser microphone
Measurement level range	5 ranges in 10-dB step :30 ~ 90dB , 40 ~ 100dB , 50 ~ 110dB , 60 ~ 120dB , 70 ~ 130dB
Digital display	4 digit LCD , 0.1dB resolution, updated every 1s
Quasi-analog bar indicator	1-dB steps, 60dB display range , updated every 0.125s
Display Warning function	
Overrange indicator	Displayed at the upper limit
Underrange indicator	Displayed at the lower limit
Analog AC / DC output	2Vrms (at full scale) , 10mVDC / dB
Power supply	Four 1.5V LR-6/AA size cell, AC adaptor
Battery Life	about 24 hours
Operating temperature , humidity	-10°C to 50°C (14°F to 122°F) R.H. < 90% non-condensing
Dimensions	265 (L) × 72(W) × 21(H)mm, (10.4" L × 2.8" W × 0.8" H)
Weight	Approx. 310g
Accessories	Instruction manual , Battery , Carrying case , Adjustment screwdriver , Software , Wind shield, USB connecting cable, 3.5ψ plug
Optional accessories	Microphone extension cable, AC Adaptor